



Perfect solution for retail stores , hotels, bars and restaurant, etc.
Cloud based operation, easy to install.

Open Sign – OS/SI Series



Module:



Feature:



Certificates:



Feature: >>>

1. Plug and Play
2. Support local and Cloud (Internet) control
3. Ethernet, USB, 3G , 4G & Wi-Fi optional
4. Energy Saving
5. AC to DC power supply, safe working voltage
6. NO additional structure needed for installation



PRODUCT SPECIFICATION

Item dimension	800 x 320 x 70		800 x 560 x 70	
Model	OS-P3	OS-P4	SI-P3	SI-P4
Pixel Pitch (mm)	3	4	3	4
Pixel Density (dot/m ²)	111,111	62500	111,111	62500
LED Type	SMD2121	SMD2121	SMD2121	SMD2121
Module Size (W x H x D)mm	240 x 240 x 15	240 x 240 x 15	240 x 240 x 15	240 x 240 x 15
Module Resolution (W x H)	80 x 80	60 x 60	80x 80	60 x 60
Module Weight (Kg)	0.52	0.72	0.52	0.72
Power Consumption per Module (W)	42	37	42	37
Driver Mode (Scan)	1/16	1/15	1/16	1/15
Brightness (cd/m ²)	≥1,500	≥1500	≥1,500	≥1500
Grey Scale (bits)	16			
Refresh Rate (Hz)	≥960			
Unit Size (W x H x D)mm	800 x 320x70		800 x 560 x 70	
Display Size (W x H)mm	720 x 240		720 x 480	
Display Resolution (W x H)	240 x 80	180 x 60	240 x 160	180 x 120
Unit Weight (Kg/pc)	8		13	
Max Power Consumption (W/m ²)	≤700		≤700	
Average Power consumption (W/m ²)	245		245	
Viewing Angle	Degree: H		120°	
	Degree: V		120°	
Mini View Distance (m)	3		3	
Use Temperature(°C)	Operating		-10°C~40°C/14°F~104°F	
	Storage		-20°C~50°C/-4°F~122 °F	
Input Voltage	100~240V			
Input Power Frequency (Hz)	50Hz-60Hz			
Failure Rate	<1/100,000			
Control Type	Network, USB, 3G , 4G & Wifi optional			
Life Span (hrs)	100,000			
IP Level (Front / Rear)	IP20 / IP20			

Main technical Parameters

Remark: Specifications are subject to change without notice.



105-6091 Dyke Rd., Richmond, BC V7E 3R3
Canada



Tel: (604) 285-5010
Fax: (604) 447-8647



E-mail: sales@leaderled.ca
Web: www.leaderled.ca



International hotline:

86-755-2359 0202